

FELLING TRAILERS, INC.

1525 Main Street South, Sauk Centre, MN 56378 Phone: 800-245-2809 – www.felling.com



2600-F

ATTENTION: Alex Drakely Ship To:

Trans Equipment Co. Inc 4423 Oregon Pike

Ephrata, Pennsylvania 17522

PO# Quote Date Order Date Order Status

Quote

Shipping Notes:

Notes:

Customer Info

Phone:

FAX:

Sales Person

717-859-2095

Bill to: Trans Equipment Co. Inc

Reference No: 228050LAE

Customer Unit/Stock:

Phone:

717-859-2095 Ephrata, Pennsylvania 17522 FAX:

Appx Completion
Other Charge
Product ID

63 (weeks)

FT-60-3 LP Deck Over -

Ramp

Serial No

Drawing No: OVL Length: 40
Copy No: Appx Wgt +/-:
Part No: 12,600 lbs

MRP No:

Smart No: 6.32640

Deck Length ✓ Add Deck Length 2 Feet 26 Frame Type Engineered Fabricated Hi-Tensile Grade 80 Main Frame Beams with Grade 80 Ir-l Cross-Members Std 1 Beavertail ✓ Wood Inlaid Beavertail (ILO Self Cleaning Angle Iron) Feet 6 Beavertail, ✓ Double Incline Opt 1 Acc Opt 1 1 Deck Type White Oak 2" Nom Std 1 Ramps; Rear ✓ 7'X 38" Plus Tapered Approach (93" OAL) Wood Inlaid, Air Operated w/Bolt on Legs Pair 1 Appx Deck ✓ 33" Loaded, 35" Unloaded Inches 1 Height Inches 1 1 1 Width 102" OD 2 Feet 32 Tle Downs D-Rings, 1" ** Straight *** (One Set Centered on BVT) Each 16 Brakes Air, ABS 25, M, Meritor WABCO (Parking brakes on all axles) Std 1 Axles 25 K Oil Bath Std 1 Axles 25 K Oil Bath Std 1 <th>Item Type</th> <th>Options</th> <th>Description</th> <th>Add Qty</th> <th>Unit</th> <th>Total Qty</th>	Item Type	Options	Description	Add Qty	Unit	Total Qty
Engineered Fabricated Hi-Tensile Grade 80 Main Frame Beams with Grade 80 Jr.I Cross-Members Beavertail / Wood Inlaid Beavertail (ILO Self Cleaning Angle Iron) Feet 6 Beavertail, / Double Incline Opt 1 Acc Beavertail, / Double Incline Opt 1 Acc White Oak 2" Nom Std 1 Ramps; Rear / 7' X 38" Plus Tapered Approach (93" OAL) Wood Inlaid, Air Operated w/Bolt on Legs Operated w/Bolt on Legs Inches In	Base Trailer		FT-60-3 LP		Each	0
Beavertail	Deck Length	✓	Add Deck Length	2	Feet	26
Beavertail, Acc ✓ Double Incline Opt 1 Acc Acc 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 7 1 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 7 6 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Frame Type				Std	1
Acc Deck Type White Oak 2" Nom Std 1 Ramps; Rear	Beavertail	1	Wood Inlaid Beavertail (ILO Self Cleaning Angle Iron)		Feet	6
Deck Type White Oak 2" Nom Std 1 Ramps; Rear ✓ 7" X 38" Plus Tapered Approach (93" OAL) Wood Inlaid, Air Operated w/Bolt on Legs Pair 1 Appx Deck ✓ 33" Loaded, 35" Unloaded Inches 1 Height 1 1 1 Width 102" OD 2 Feet 32 Tie Downs D-Rings, 1" ** Straight ** (One Set Centered on BVT) Each 16 Brakes Air, ABS 25/1M, Meritor WABCO (Parking brakes on all axles) Std 3 Suspension 49" Spread (Spring), 9700 Hutch Std 1 Suspension 49" Spread Air Ride, Ridewell 260 with Dump Valve Axle 3 **First Axle Only** Axle 3 3 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Tires & ✓ 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot Each 12 Wheels ✓ 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot Each 12 Hitch Type 3" Adjustable 90K Pintle [C] (7/8" G 8 Bol	,	✓	Double Incline		Opt	1
Ramps; Rear						
Appx Deck ✓ 33" Loaded, 35" Unloaded Inches 1 Height Width 102" OD 2 Feet 32 Tie Downs D-Rings, 1" ** Straight ** (One Set Centered on BVT) Each 16 Brakes Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles) 5td 1 Axles 25K Oil Bath 5td 3 Suspension 49" Spread (Spring), 9700 Hutch 5td 1 Suspension 49" Spread Air Ride, Ridewell 260 with Dump Valve Axle 3 **First Axle Only** Axle 3 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Tires & ✓ 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot Each 12 Wheels Hitch Length ✓ Center of Coupler to Headboard, Appx 1 Feet 6.3 Hitch Type 3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts) 5td 1 Jack ✓ 140,000 lb Twin 2 Speed (39,000 lb Lift Capacity) Pair 1 Plug 7 Pole Semi 5td 1 Lights LED Li						1
Height Width 102" OD 2 Feet 32 Tie Downs D-Rings, 1"** Straight ** (One Set Centered on BVT) Each 16 Brakes Air, ABS 25/1M, Meritor WABCO (Parking brakes on all axles) Std 1 Axles 25K Oil Bath Std 1 Suspension 49" Spread (Spring), 9700 Hutch Std 1 Suspension 49" Spread Air Ride, Ridewell 260 with Dump Valve **First Axle Only** Axle 3 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Tires & ✓ 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot Each 12 Wheels 1 Feet 6.3 Hitch Length ✓ Center of Coupler to Headboard, Appx 1 Feet 6.3 Hitch Type 3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts) Std 1 Jack ✓ 140,000 Ib Twin 2 Speed (39,000 Ib Lift Capacity) Pair 1 Plug 7 Pole Semi Std 1 Lights LED Lights (Peterson), Sealed Wiring Harness (Sealco) Std 1 Stripe Color White Std <t< td=""><td>Ramps; Rear</td><td>✓</td><td>· · · · · · · · · · · · · · · · · · ·</td><td></td><td>Pair</td><td>1</td></t<>	Ramps; Rear	✓	· · · · · · · · · · · · · · · · · · ·		Pair	1
Width 102" OD 2 Feet 32 Tie Downs D-Rings, 1" ** Straight ** (One Set Centered on BVT) Each 16 Brakes Air, ABS 25/1M, Meritor WABCO (Parking brakes on all axles) Std 1 Axles 25K Oil Bath Std 3 Suspension 49" Spread (Spring), 9700 Hutch Std 1 Suspension ✓ 49" Spread Air Ride, Ridewell 260 with Dump Valve Axle 3 **First Axle Only** Axle 3 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Fires & Yale Only** Each 12 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Fires & Yale Only** Each 12 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Fires & Yale Only** Axle 3 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Fires & Yale Only** Yale Only** Std 1 Feet 6.3 Hitch Length Center of Coupler to Headboard, Appx 1 Feet 6.3 Hitch Type 3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts) Std		1	33" Loaded, 35" Unloaded		Inches	1
Brakes Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles) Std 1 Axles 25K Oil Bath Std 3 Suspension 49" Spread (Spring), 9700 Hutch Std 1 Suspension ✓ 49" Spread Air Ride, Ridewell 260 with Dump Valve **First Axle Only** Axle 3 Suspension ✓ Air Lift Axle (1st axle only, requires air ride on this axle) Opt 1 Tires & ✓ 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot Each 12 Wheels Each 12 Hitch Length ✓ Center of Coupler to Headboard, Appx 1 Feet 6.3 Hitch Type 3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts) Std 1 Jack ✓ 140,000 lb Twin 2 Speed (39,000 lb Lift Capacity) Pair 1 Plug 7 Pole Semi Std 1 Lights LED Lights (Peterson), Sealed Wiring Harness (Sealco) Std 1 Trailer Color ✓ Viper Red # CCA945383 (White Felling Decal) Opt 1 Standard Document Holder Std 1 Standard 5/8" Safety Chains, Grade 80 Std 1 Option ✓			102" OD	2	Feet	32
Axles25K Oil BathStd3Suspension49" Spread (Spring), 9700 HutchStd1Suspension✓ 49" Spread Air Ride, Ridewell 260 with Dump Valve **First Axle Only**Axle3Suspension✓ Air Lift Axle (1st axle only, requires air ride on this axle)Opt1Tires & Wheels✓ 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub PilotEach12Hitch Length✓ Center of Coupler to Headboard, Appx1Feet6.3Hitch Type3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts)Std1Jack✓ 140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)Pair1Plug7 Pole SemiStd1LightsLED Lights (Peterson), Sealed Wiring Harness (Sealco)Std1Stripe ColorWhiteStd1StandardDocument HolderStd1StandardDocument HolderStd1Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable lotted)Opt1Option✓ Toolbox, Extended as far forward as possible (with lockable lotted)Opt1	Tie Downs		D-Rings, 1" ** Straight ** (One Set Centered on BVT)		Each	16
Suspension49" Spread (Spring), 9700 HutchStd1Suspension✓ 49" Spread Air Ride, Ridewell 260 with Dump Valve **First Axle Only**Axle3Suspension✓ Air Lift Axle (1st axle only, requires air ride on this axle)Opt1Tires & Wheels✓ 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub PilotEach12Hitch Length✓ Center of Coupler to Headboard, Appx1Feet6.3Hitch Type3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts)Std1Jack✓ 140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)Pair1Plug7 Pole SemiStd1LightsLED Lights (Peterson), Sealed Wiring Harness (Sealco)Std1Stripe ColorWhiteStd1StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd1Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Brakes		Air, ABS 2S/1M, Meritor WABCO (Parking brakes on all axles)		Std	1
Suspension 49" Spread Air Ride, Ridewell 260 with Dump Valve **First Axle Only** Axle Suspension Air Lift Axle (1st axle only, requires air ride on this axle) Opt Tires & 245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot Bach	Axles		25K Oil Bath		Std	3
First Axle Only Suspension	Suspension		49" Spread (Spring), 9700 Hutch		Std	1
Tires &	Suspension	1	•		Axle	3
WheelsHitch Length✓ Center of Coupler to Headboard, Appx1Feet6.3Hitch Type3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts)Std1Jack✓ 140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)Pair1Plug7 Pole SemiStd1LightsLED Lights (Peterson), Sealed Wiring Harness (Sealco)Std1Trailer Color✓ Viper Red # CCA945383 (White Felling Decal)Opt1Stripe ColorWhiteStd1StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Suspension	✓	Air Lift Axle (1st axle only, requires air ride on this axle)		Opt	1
Hitch Type 3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts) Std 1 Jack ✓ 140,000 lb Twin 2 Speed (39,000 lb Lift Capacity) Pair 1 Plug 7 Pole Semi Std 1 Lights LED Lights (Peterson), Sealed Wiring Harness (Sealco) Std 1 Trailer Color ✓ Viper Red # CCA945383 (White Felling Decal) Opt 1 Stripe Color White Std 1 Standard Document Holder Std 1 Standard Document Holder Std 1 Standard Standard Hitch and 1 in front of Axles on Roadside Standard St8 Safety Chains, Grade 80 Std 1 Option ✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitch		✓	245/70R 17.5 J, 8 Bolt [17.5 x 6.75] Hub Pilot		Each	12
Jack✓140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)Pair1Plug7 Pole SemiStd1LightsLED Lights (Peterson), Sealed Wiring Harness (Sealco)Std1Trailer Color✓ Viper Red # CCA945383 (White Felling Decal)Opt1Stripe ColorWhiteStd1StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Hitch Length	1	Center of Coupler to Headboard, Appx	1	Feet	6.3
Plug7 Pole SemiStd1LightsLED Lights (Peterson), Sealed Wiring Harness (Sealco)Std1Trailer Color✓ Viper Red # CCA945383 (White Felling Decal)Opt1Stripe ColorWhiteStd1StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Hitch Type		3" Adjustable 90K Pintle [C] (7/8" Gr 8 Bolts)		Std	1
LightsLED Lights (Peterson), Sealed Wiring Harness (Sealco)Std1Trailer Color✓ Viper Red # CCA945383 (White Felling Decal)Opt1Stripe ColorWhiteStd1StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Jack	1	140,000 lb Twin 2 Speed (39,000 lb Lift Capacity)		Pair	1
Trailer Color✓ Viper Red # CCA945383 (White Felling Decal)Opt1Stripe ColorWhiteStd1StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Plug		7 Pole Semi		Std	1
Stripe ColorWhiteStd1StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Lights		LED Lights (Peterson), Sealed Wiring Harness (Sealco)		Std	1
StandardDocument HolderStd1Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓ Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Trailer Color	✓	Viper Red # CCA945383 (White Felling Decal)		Opt	1
Standard2 Steps,1 on the Standard Hitch and 1 in front of Axles on RoadsideStd2Standard5/8" Safety Chains, Grade 80Std1Option✓Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitchOpt1	Stripe Color		White		Std	1
Roadside Standard 5/8" Safety Chains, Grade 80 Std 1 Option Toolbox, Extended as far forward as possible (with lockable latch) in a-frame area of hitch	Standard		Document Holder		Std	1
Option Toolbox, Extended as far forward as possible (with lockable Opt 1 latch) in a-frame area of hitch	Standard		• •		Std	2
latch) in a-frame area of hitch	Standard		5/8" Safety Chains, Grade 80		Std	1
GVWR 71,400 lbs Std 1	Option	✓			Opt	1
	GVWR		71,400 lbs		Std	1



FELLING TRAILERS, INC.

1525 Main Street South, Sauk Centre, MN 56378 Phone: 800-245-2809 – www.felling.com



2600-F



MSO's are not released until Payment Received



FOB IF NO FREIGHT charged

** FET Tax may apply on 26,000 lb GVWR and above **

Please sign and date your acceptance of this quote:						

PRICING MAY BE SUBJECT TO MARKET ADJUSTMENT AT TIME OF INVOICE