Aluminum Flatbed Trailer									
		7			Qu	ote # 07262201SA			
		Custon	mer PO#:	Trans Equipment Co., Inc.	Total Units Ord	lered: 1			
			4423 Oregon Pike		Serial Number:	P1588556			
317 E Broadway St. Dover, OH 44622			Ephrata, PA 17522 (717) 859-2095		Model Number: XP55531022				
· · · · · · · · · · · · · · · · · · ·		Sales	ales Person:		Model Year: 2023				
		C	Customer:		Delivery Date:	IN STOCK			
BASE MODEL:		GVWR:	:						
Length: 5	<sup>3'</sup> Couple	er Plate: 5/16"	" Stl Galv - Std	Coil Pack/Well:	Coil Pack (	M) - Std			
Width: 10	D2 King Pin	Setting:	30" - Std	Decking	Alum, 2 Nailers - Std				
Model: XP	Final Lub	e Liner:	No	Crush Res. Tech:	6 ft Mid Coil Pack - 4 Voids				
Neck: 1	1" Coupler	Setting:	48" - Std	Landing Gear:	Jost Alum – 10 yr Warranty				
Arch: 5	T Xmember	Space:	18" - Std						
Bulkhead:		None - Std							
Side Rail:	J-Hook wit	th 48" Pocket Spacir	ng - Std	Winch Tra	ack "LL": Yes Rope	Hooks: None			
Sliding Winche	s: None				Chain Tie	Downs: None			
Winch Strap	os: None				Extreme	T-Hook: None			
Cargo Hooks: None J-Hook Tie Downs						Downs: None			
Fixed Winche	es: None								
AXLE AND WHEEL OPTIONS									
AXLE AND WHEEL (	OPTIONS								
AXLE AND WHEEL ON NO. of Axles:	OPTIONS 2								
	2	Warranty:	AxlePak5 - Std	Lift Axle (Optional):	No Slide (Oj	ptional): Yes			
No. of Axles:	2	Warranty:	AxlePak5 - Std Alum Clean		No Siide (Oj 295/75R 22.5 Ri				
No. of Axles: Rear Axle	2 e: MTM23T Wheels: 22.5x8.25		Alum Clean						
No. of Axles: Rear Axle	2 e: MTM23T Wheels: 22.5x8.25	Finish:	Alum Clean	Buff Tires:					
No. of Axles: Rear Axle	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide,	Finish:	Alum Clean	Buff Tires:		M272 Cooper			
No. of Axles: Rear Axle	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide,	Finish:	Alum Clean Suspension	Buff Tires: Control Notes: Lift Axle (Optional):	295/75R 22.5 R	M272 Cooper			
No. of Axles: Rear Axle Front Axle	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Siide, e: MTM23T Wheels: 22.5x8.25	Finish:	Alum Clean Suspension AxlePak5 - Std Alum Clean	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires:	295/75R 22.5 R	M272 Cooper			
No. of Axles: Rear Axle Front Axle	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Silde, e: MTM23T Wheels: 22.5x8.25 Spacing:	Finish: 41' KP, 40' KP Warranty: Finish: 122	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift	295/75R 22.5 R Yes Slide (Op 295/75R 22.5 R	M272 Cooper			
No. of Axles: Rear Axle Front Axle Options: Brake	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: 22.5x8.25 Spacing:	Finish:	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension Hub:	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift DuraLite - Std	295/75R 22.5 R Yes Slide (Op 295/75R 22.5 R 295/75R 22.5 R thru 7 way ISO Black and Ball Value	M272 Cooper ptional): No M272 Cooper ve mounted on Frame in Box			
No. of Axles: Rear Axle Front Axle Options: Brake Finis	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: 22.5x8.25 Spacing: 22.5x8.25 spacing: 22.5x8.25 spacing: 22.5x8.25	Finish: 41' KP, 40' KP Warranty: 7 Finish: 122 e Coat - Std	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension Hub: YAK Cylinder:	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift DuraLite - Std Yes	Yes Slide (O) 295/75R 22.5 R Slide (O) 295/75R 22.5 R 295/75R 22.5 R thru 7 way ISO Black and Ball Val	M272 Cooper  ptional): No  M272 Cooper  ve mounted on Frame in Box  None			
No. of Axles: Rear Axle Front Axle Options: Brake	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: 22.5x8.25 Spacing: 22.5x8.25 spacing: 22.5x8.25 spacing: 22.5x8.25	Finish: 41' KP, 40' KP Warranty: 7 Finish: 122 e Coat - Std	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension Hub:	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift DuraLite - Std	295/75R 22.5 R Yes Slide (Op 295/75R 22.5 R 295/75R 22.5 R thru 7 way ISO Black and Ball Value	M272 Cooper ptional): No M272 Cooper ve mounted on Frame in Box			
No. of Axles: Rear Axle Front Axle Options: Brake Finis EC	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: 22.5x8.25	Finish: 41' KP, 40' KP Warranty: 7 122 e Coat - Std td Rear Axte	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension Hub: YAK Cylinder: Axle Covers: le Dump:	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift DuraLite - Std Yes	Yes Slide (O) 295/75R 22.5 R Slide (O) 295/75R 22.5 R 295/75R 22.5 R thru 7 way ISO Black and Ball Val	M272 Cooper  ptional): No  M272 Cooper  ve mounted on Frame in Box  None  Yes - Std			
No. of Axles: Rear Axle Front Axle Options: Brake Finis EC	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: es Disc Brak h: Galv. / Black Soft ( U: 4S/2M - S	Finish: 41' KP, 40' KP Warranty: 7 122 e Coat - Std td Rear Axte	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension Hub: YAK Cylinder: Axle Covers:	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift DuraLite - Std Yes Front Axle	Yes Slide (O) 295/75R 22.5 R Slide (O) 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R	M272 Cooper  ptional): No  M272 Cooper  ve mounted on Frame in Box  None  Yes - Std			
No. of Axles: Rear Axle Front Axle Options: Brake Finis EC	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: 22.5x8.25	Finish: 41' KP, 40' KP Warranty: 7 122 e Coat - Std td Rear Axte	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension Hub: YAK Cylinder: Axle Covers: le Dump:	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift DuraLite - Std Yes Front Axle	Yes Slide (O) 295/75R 22.5 R Slide (O) 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R	M272 Cooper  ptional): No  M272 Cooper  ve mounted on Frame in Box  None  Yes - Std			
No. of Axles: Rear Axle Front Axle Options: Brake Finis EC Controls: Auxille	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: 22.5x8.25	Finish:	Alum Clean Suspension AxlePak5 - Std Alum Clean Suspension Hub: YAK Cylinder: Axle Covers: le Dump:	Buff Tires: Control Notes: Lift Axle (Optional): Buff Tires: Control Notes: Front Axle Lift DuraLite - Std Yes Front Axle	Yes Slide (O) 295/75R 22.5 R Slide (O) 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R	M272 Cooper  ptional): No  M272 Cooper  ve mounted on Frame in Box  None  Yes - Std			
No. of Axles: Rear Axle Front Axle Options: Brake Finis EC Controls: Auxille Lights / Decals / Bur	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing:	Finish: 41' KP, 40' KP Warranty: Finish: 122 e Coat - Std td Rear Axle Glac Rail	Alum Clean Suspension AxlePak5 - Std Alum Clean Alum Clean Suspension Hub: YAK Cylinder: Axle Covers: le Dump: clea	Buff     Tires:       Control Notes:	Yes Slide (Op 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 2010 295/75R 22.5 R 2010 2010 2010 2010 2010 2010 2010 201	M272 Cooper  ptional): No  M272 Cooper  ve mounted on Frame in Box  None  Yes - Std  7 Way ISO Brown.			
No. of Axles: Rear Axle Front Axle Options: Brake Finis EC Controls: Auxille Lights / Decals / Bur Marker Light	2 e: MTM23T Wheels: 22.5x8.25 Spacing: 3 Pos Slide, e: MTM23T Wheels: 22.5x8.25 Spacing: 22.5x8.25	Finish: 41' KP, 40' KP Warranty: Finish: 122 e Coat - Std Coat - Std	Alum Clean Suspension AxlePak5 - Std Alum Clean Alum Clean Suspension Hub: YAK Cylinder: Axle Covers: le Dump: clea	Buff       Tires:         Control Notes:	Yes Slide (Op 295/75R 22.5 R Slide (Op 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 295/75R 22.5 R 205/75R 205/75R 205/75R 200/75R 205/75R 200/75R 200/75R 200/75R 200/75R	M272 Cooper  ptional): No  M272 Cooper  ve mounted on Frame in Box  None  Yes - Std  7 Way ISO Brown.  No			

Accesso	ories					
	Toolboxes: 1					
	Toolbox 1:	24" x 24" x 60" w/ Polished Doors (Cam	Lock, Piano Hinge)	Location:	CS - Ahead of	Front Axle
Duni	nage Racks: 1					
	Dunnage Rack 1:	108" (Std)		Location:	RS - Behind La	anding Gear
	Tire Carrier: CS - Behind La	anding Gear Load Scale:	None - Std		Quick Release Valve:	None - Std
	Forklift Kit: No	Log Pockets: None	Coil Stops: No	one	Mudflaps	Behind All Axles
Addition	nal Options Requiring Quotati	on:				
Additiona	al Options Requested:			+	/- Price	+/- Weight
1)						
2)						
3)						
4)						
5)						
6)						
7)						
8)						
ı '						
9)						
10)						
Notes and	d Comments:					
					Total Unit Price:	\$
					+Tax/FET:	
					Sub Total:	\$
					Quantity Ordered:	1 Unit(s)
					Grand Total:	\$
						Tare Weight (+/- 3%)
x		х				9081 lbs
<u> </u>	Authorized Purchase S		of Signature *Pricing	Good for 30 Days f	rom Quote	