

317 E Broadway St. Dover, OH 44622

330-440-0026 • 234-542-6026 (Fax)

Aluminum Flatbed Trailer

January, 13 2023

Customer PO#: EX020722-001 thru EX020722-004

Dealer:

Trans Equipment Co., Inc.

4423 Oregon Pike Ephrata, PA 17522 (717) 859-2095

Sales Person:

Stock XP55 48ft Drum Brz

Quote #

09272204SA

Total Units Ordered:

6

 Serial Number:
 R1588204-588205

 Model Number:
 XP55481022

 Model Year:
 2024

				Customer: St	ock XP55 48ft D	rum Brakes	ι	Delivery Date:	IN STOCK			
BASE MODEL: GVWR:												
Length:	48'	Coupl	er Plate: 5	i/16" Stl Galv - Std	С	Coil Pack/Well:		Coil Pack (M) - Std				
Width:	102	King Pin	Setting:	30" - Std		Decking		Alum, 2 Nailers - Std				
Model:	XP55	Final Luk	e Liner:	No	Crus	sh Res. Tech:	6 ft Mid Coil Pac		/oids			
Neck:	11"	Coupler	Setting:	48" - Std	L	anding Gear:		Jost Alum – 10 yr Warranty				
Arch:	5"	Xmember Space:		18" - Std								
Bulkhead:		None - Std										
Side Rail:		J-Track with 48" Pocket Spacing - Std Winch Track "LL": Both Sides Rope Hooks: None										
Slidir	ng Winches:											
Winch Straps:		None						Extreme T-Hook	:: None			
Cargo Hooks:		None						J-Hook Tie Downs	:: None			
Fixed Winches:		None										
AXLE AND WHEEL OPTIONS												
No. of Axles: 2												
D	ear Axle:	MTM23T	Warranty:	AxlePak5 - Std	AxlePak5 - Std Lift Axle (Optional): N			Slide (Optional)	ı: No			
Wheels			Finish:	Alum Clean	·	Tires:		95/75R 22.5 RH652 F				
Spacing:			26			Tiles.	2557517 22.5111052 170407					
Spacing: 26 Suspension Control Notes:												
Fre	ont Axle:	MTM23T	Warranty:	AxlePak5 - Std	L	ift Axle (Optional):	Yes	Slide (Optional)	: No			
	Wh	eels: 22.5x8.25	Finish:	Alum Clean	Buff	Tires:	2	95/75R 22.5 RH652 F	RoadX			
Spacing		cing:	122 Susper		on Control Notes:							
	_											
Options:	Brakes	16.5" x 7" Extended	Service (Std)	Hub:	Dural	ite - Std	D	rum: Ca	astlite			
Finish:			Galv. / Black Soft Coat - Std		ylinder: Dual Leveling		Tire Infla		one			
	ECU:	4S/2M - 5	Std	Axle Covers:	All	Axles	Dust Shie	elds: No	- Std			
Controls:	Auxillery F	Plug: 7-Way ISO	Rear	Axle Dump:	Yes	Control Notes:						
Dump '		mp Valve (All Bags):	(Gladhand Disconnect								
Lights / Deca	als / Bumpe	ers										
Marker Lights:			9 Lights, In Rail			Clear Lens Lights: Yes		I Air/Electric:	No			
R	tear Lights:	4L-5L-4	4L-5L-4L w/ S.S. Cover & Rings			Aux Plug: No	ne Aux	tillery Lights:	None			
Decals:			Conspicuity Tape, Installed on Rub Rail - STD				Wide	Load Lights:	No			
	Bumper:	ICC 4-Post Enclosed, Extreme Logo & Short Flaps					Do	ck Bumpers:	2			

Accessories								
Toolboxes:	2							
Toolbox 1:	24" x 24" x 60" w	Polished Doors (Cam Lock, Piano	Hinge)	Location:	RS - Between Spread			
Toolbox 2:		24" x 24" x 60" w/ Polished Doors (Cam Lock, Piano Hinge)				n Spread		
TOOIDOX 2.	24 X 24 X 00 W/	24 X 24 X 00 W/ Folished Dools (Calli Lock, Flatio Hilige)			CO - Detween	Topreau		
Dunnage Racks:	0	nage Racks to be Inst	be Installed***					
Tire Carrier:			ige w/ Valves in Box		Quick Release Valve:	None - Std		
Forklift Kit:	No Log Pockets:	None	Coil Stops: No	ne	Mudflaps	Behind All Axles		
Additional Options Requirir	ng Quotation:							
Additional Options Requested:					+/- Price	+/- Weight		
1)								
2)								
3)								
4)								
5)								
6)								
7)								
8)								
, L								
9)								
10)								
Notes and Comments:					List Price:			
					Surcharge:			
					Discount (per Unit):			
					Total Unit Price:			
					+Tax/FET:			
					Sub Total:			
					Quantity Ordered:	6 Unit(s)		
					Grand Total:			
					ı			
						Tare Weight (+/- 3%)		
x			_ x			8232 lbs		
SA-FM-02 (Rev 1.9) Authorized Purchase Signature Date of Signature *Pricing Good for 30 Days from Quote								